



www.md-europe.eu

# MDV-205T

ST.ST.BALL VALVES	RVS KOGELAFSLUITER
<b>SPECIFICATIONS:</b> 3 piece, full bore face-to-face EN 16722 tabel 1-M3 thread f/f ISO 228-1G <u>nominal pressure:</u> DN 8 (1/4") - DN 50 (2"): PN63 DN 65 (2.1/2") - DN 100(4"): PN40 PTFE seats and seals temperature -20°C upto 180°C	<b>SPECIFICATIES:</b> 3-delig, volle doorlaat inbouw lengte EN 16722 tabel 1-M3 draad bi-bi ISO 228-1G <u>nominale druk</u> DN 8 (1/4") - DN 50 (2"): PN63 DN 65 (2.1/2") - DN 100(4"): PN40 PTFE zittingen en afdichtingen temperatuur -20°C tot +180°C

DIMENSIONS	P	L	BL	CL	H	W									kg/pc	CF8	CF8M
AFMETINGEN	mm	mm	mm	mm	mm	mm									kg/st	304	316
DN 8	1/4"	11	55	21	17	53	100								0,35	●	○
DN 10	3/8"	12,5	60	21	19,5	53	100								0,35	●	○
DN 15	1/2"	15	75	26	24,5	66	130								0,56	○	●
DN 20	3/4"	20	80	32	24	68,5	130								0,75	○	●
DN 25	1"	25	90	38	26	76	165								1,08	○	●
DN 32	1.1/4"	32	110	48	31	82	165								1,73	○	●
DN 40	1.1/2"	38	120	54	33	93	190								2,56	○	●
DN 50	2"	50	140	67	36,5	103	190								3,20	○	●
DN 65	2.1/2"	64	185	87	49	135	250								7,35	○	○
DN 80	3"	76	205	104	50,5	144	250								11,21	○	○
DN 100	4"	100	240	126	57	203	300								20,30	○	○

nr	part name	naam onderdeel	CF8	CF8M	pc
			304	316	st
1	body	huis	ASTM A 351 CF8	ASTM A 351 CF8M	1
2	ball	kogel	ASTM A 182 F316	ASTM A 182 F316	1
3	Seat	zitting	PTFE	PTFE	2
4	Gasket	pakking	PTFE	PTFE	2
5	End-Cap	eindkap	ASTM A 351 CF8	ASTM A 351 CF8M	2
6	spring washer	veerring	ASTM 276 SS304	ASTM 276 SS304	4/6 <sup>1</sup>
7	bolt nuts	moeren	A2-70 (SS304)	A2-70 (SS304)	4/6 <sup>1</sup>
8	body bolt	bouten	A2-70 (SS304)	A2-70 (SS304)	4/6 <sup>1</sup>
9	plunger spring	plunjer veer	ASTM 276 SS316	ASTM 276 SS316	2
10	anti static ball	antistatischekogel	ASTM 276 SS316	ASTM 276 SS316	2
11	stem	spindel	ASTM 276 SS316	ASTM 276 SS316	1
12	thrust washer	dichtingsring	PTFE	PTFE	1
14	stem packing	spindelpakking	PTFE	PTFE	1
15	gland	pakkingdrukker	ASTM 276 SS304	ASTM 276 SS304	1
16	nut	moer	A2-70 (SS304)	A2-70 (SS304)	1
17	crown washer	kroonring	ASTM 276 SS304	ASTM 276 SS304	1
18	spring washer	veerring	ASTM 276 SS304	ASTM 276 SS304	1
19	stem nut	spindelmoer	A2-70 (SS304)	A2-70 (SS304)	1
21	locking pad	vergrendeling	ASTM A 240 tp 201	ASTM A 240 tp 201	1
22	handle	hendel	ASTM A 240 tp 201	ASTM A 240 tp 201	1
23	handle cover	handgreep	PVC	PVC	1

- stock, s.u.
  - ex mill
- 
- voorraad, m.o.
  - af fabriek

<sup>1</sup> 6 pcs for DN100

COLOUR HANDLE COVER: standard : yellow Options : red, green, blue, grey, white

KLEUR HANDGRIEP : standaard: geel. Opties : rood, groen, blauw, grijs, wit.



www.md-europe.eu

# MDV-205T



pressure - temperature

druk - temperatuur

