



www.md-europe.eu

MDV-GT

CAST ST.ST.GATE VALVES	GEGOTEN RVS SCHUIFAFSLUITER
SPECIFICATIONS:	SPECIFICATIES:
full bore, non-rising stem screwed-in bonnet, solid st.st. wedge disc thread f/f ISO 228-1G <i>also available ex mill as MDV-GTN with NPT thread</i> <u>nominal pressure</u> DN 8 (1/4") - DN25 (1"): PN63 DN 32 (1.1/4") - DN 50 (2"): PN40 PTFE seats and seals temperature -20°C upto 180°C	volle doorlaat, niet rijzende spindel geschroefde deksel, massieve rvs schuif draad bi-bi ISO 228-1G <i>ook leverbaar af fabriek als MDV-GTN met NPT draad</i> <u>nominale druk</u> DN 8 (1/4") - DN25 (1"): PN63 DN 32 (1.1/4") - DN 50 (2"): PN40 PTFE zittingen en afdichtingen temperatuur -20°C tot +180°C

DIMENSIONS													kg/pc	CF8	CF8M		
AFMETINGEN		P	H(open)	L	L2	W											
DN	"	mm	mm	mm	mm	mm									kg/st	304	316
DN 8	1/4"	7	90	55,0	27,5	70									0,38	o	o
DN 10	3/8"	10	90	55,0	27,5	70									0,38	o	o
DN 15	1/2"	15	92	55,0	27,5	70									0,38	o	o
DN 20	3/4"	20	97	60,5	30,0	70									0,50	o	o
DN 25	1"	25	109	65,5	32,5	80									0,70	o	o
DN 32	1.1/4"	32	124	76,5	37,5	80									1,05	o	o
DN 40	1.1/2"	40	146	85,5	42,5	90									1,40	o	o
DN 50	2"	50	162	95,5	47,5	100									2,05	o	o

nr	part name	naam onderdeel	CF8	CF8M	pc
			304	316	st
1	body	huis	ASTM A 351 CF8	ASTM A 351 CF8M	1
2	disc	schuif	ASTM A 351 CF8M	ASTM A 351 CF8M	1
4	body seal	pakking	PTFE	PTFE	1
5	bonnet	deksel	ASTM A 351 CF8	ASTM A 351 CF8M	1
6	stem	spindel	ASTM 276 SS316	ASTM 276 SS316	1
7	stop ring	stop ring	PTFE	PTFE	1
8	stem packing	spindelpakking	PTFE	PTFE	1
9	gland bushing	pakkingsdrukker	ASTM 276 SS304	ASTM 276 SS304	1
11	stem nut	spindelmoer	A2-70 (SS304)	A2-70 (SS304)	1
13	handweel	handwiel	mico steel	mico steel	1
14	name plate	naamplaat	aluminium	aluminium	1
15	bonnet nut	dekselmoer	ASTM 276 SS304	ASTM 276 SS304	1
20	spring washer	veerring	ASTM 276 SS304	ASTM 276 SS304	1

- stock, s.u.
 - o ex mill
-
- voorraad m.o
 - o af fabriek

COLOUR HAND WHEEL: standard red
 KLEUR HANDWIEL : standaard rood



