



www.md-europe.eu

# MDV-SC

## CAST ST.ST. SWING TYPE CHECK VALVE

## GEGOTEN RVS SWING TYPE TERUGSLAGKLEP

### SPECIFICATIONS:

full bore  
 screwed in-bonnet, st.st. disc  
 f/f thread ISO 228-1G  
*also available ex mill as MDV-SCN with NPT thread*  
nominal pressure  
 DN 8 (1/4") - DN25 (1"): PN63  
 DN 32 (1.1/4") - DN 50 (2"): PN40  
 PTFE seats and seals  
 temperature -20°C upto 180°C

### SPECIFICATIES:

volle doorlaat  
 geschroefde deksel, rvs klep  
 bi-bi draad ISO 228-1G  
*ook leverbaar af fabriek als SCN met NPT draad*  
nominale druk  
 DN 8 (1/4") - DN25 (1"): PN63  
 DN 32 (1.1/4") - DN 50 (2"): PN40  
 PTFE zittingen en afdichtingen  
 temperatuur -20°C tot +180°C


### DIMENSIONS

AFMETINGEN		P	H	L	T1/T2												kg/st	CF8	CF8M
DN	"	mm	mm	mm	mm												kg/pc	304	316
DN 8	1/4"	11	42	65	12												0,35	o	o
DN 10	3/8"	13	42	65	12												0,35	o	o
DN 15	1/2"	15	42	65	13												0,33	o	o
DN 20	3/4"	20	51	80	15												0,42	o	o
DN 25	1"	25	60	90	18												0,70	o	o
DN 32	1.1/4"	32	66	105	19												1,00	o	o
DN 40	1.1/2"	40	75	120	20												1,50	o	o
DN 50	2"	50	80	140	22												2,10	o	o

nr	part name	naam onderdeel	CF8	CF8M	pc
			304	316	st
1	body	huis	ASTM A 351 CF8	ASTM A 351 CF8M	1
2	disc	klep	ASTM A 351 CF8M	ASTM A 351 CF8M	1
3	plug seal	plug pakking	PTFE	PTFE	1
4	body seal	pakking	PTFE	PTFE	1
5	bonnet	deksel	ASTM A 351 CF8	ASTM A 351 CF8M	1
6	hanger pin	klep pin	ASTM 276 SS316	ASTM 276 SS316	1
7	plug	plug	ASTM 276 SS316	ASTM 276 SS316	1

- stock, s.u.
- o ex mill

- voorraad m.o
- o af fabriek



# MDV-SC

