



www.md-europe.eu

# MDV-YS

## CAST ST.ST. STRAINER

### SPECIFICATIONS:

screwed-in bonnet, Y type  
 full bore, st.st. screen  
 f/f ISO 228-1G  
*also available ex mill as MDV-YSN with NPT thread*  
nominal pressure  
 DN 8 (1/4") - DN25 (1"): PN63  
 DN 32 (1.1/4") - DN 50 (2"): PN40  
 PTFE seats and seals  
 temperature -20°C upto 180°C

## GEGOTEN RVS FILTER

### SPECIFICATIES:


geschroefde deksel, Y-type  
 volle doorlaat, RVS zeef  
 draad bi-bi ISO 228-1G  
*ook leverbaar af fabriek als MDV-YSN met NPT draad*  
nominale druk  
 DN 8 (1/4") - DN25 (1"): PN63  
 DN 32 (1.1/4") - DN 50 (2"): PN40  
 PTFE zittingen en afdichtingen  
 temperatuur -20°C tot +180°C

### DIMENSIONS

AFMETINGEN		P	L	H	B	E	d											kg/st	CF8	CF8M
DN	"	mm	mm	mm	mm	mm	mm													
DN 8	1/4"	10	65	48	24	2	1											0,30	o	o
DN 10	3/8"	12	65	48	24	2	1											0,30	o	o
DN 15	1/2"	15	65	48	26	2	1											0,30	o	o
DN 20	3/4"	20	80	55	33	2	1											0,50	o	o
DN 25	1"	25	90	70	41	2	1											0,96	o	o
DN 32	1.1/4"	32	105	74	49	2	1											1,20	o	o
DN 40	1.1/2"	40	120	82	56	2	1											1,80	o	o
DN 50	2"	50	140	95	69	2	1											2,50	o	o

nr	part name	naam onderdeel	CF8	CF8M	pc
			304	316	st
1	body	huis	ASTM A 351 CF8	ASTM A 351 CF8M	1
2	screen	zeef	ASTM 276 SS316	ASTM 276 SS316	1
3	body seal	packing	PTFE	PTFE	1
4	bonnet	deksel	CF8	CF8M	1

- stock, s.u.
- o ex mill
- voorraad m.o
- o af fabriek





www.md-europe.eu

# MDV-YS

