



www.md-europe.eu

MDV-368T

ST.ST.BALL VALVES	RVS KOGELAFSLUITER
SPECIFICATIONS:	SPECIFICATIES:
2 piece, full bore, ISO 5211 direct-mount top flange face-to-face EN 16722 tabel 1-M3 thread f/f ISO 228-1G <i>also available ex mill as MDV-368NT with NPT thread</i> <u>nominal pressure:</u> DN 15 (1/2") - DN 50(2"): PN63 DN 65 (2.1/2") - DN 80 (3"): PN 40 PTFE seats and seals temperature -20°C upto 180°C	2-delig, volle doorlaat, ISO 5211 direct-mount top flens inbouw lengte EN 16722 tabel 1-M3 draad bi-bi ISO 228-1G <i>ook leverbaar af fabriek als MDV-368NT met NPT draad</i> <u>nominale druk:</u> DN 15 (1/2") - DN 50(2"): PN63 DN 65 (2.1/2") - DN 80 (3"): PN 40 PTFE zittingen en afdichtingen temperatuur -20°C tot +180°C

DIMENSIONS	P	L	H	H3	W	h	S	ISO 5211						kg/st	CF8	CF8M	
								F	PCD	Ø	F	PCD	Ø				kg/pc
DN 15	1/2"	15	75	64	35	120	6	9	F03	36	6x4	F04	42	6x4	0,51	o	o
DN 20	3/4"	20	80	70	42	120	6	9	F03	36	6x4	F04	42	6x4	0,68	o	o
DN 25	1"	25	90	81	53	165	8	11	F04	42	6x4	F05	50	7x4	1,04	o	o
DN 32	1.1/4"	32	110	88	59	165	8	11	F04	42	6x4	F05	50	7x4	1,75	o	o
DN 40	1.1/2"	38	120	117	68	190	10	14	F05	50	7x4	F07	70	9x4	2,65	o	o
DN 50	2"	50	140	126	79	190	10	14	F05	50	7x4	F07	70	9x4	4,12	o	o
DN 65	2.1/2"	65	185	145	98	250	12	17	F07	70	9x4	F10	102	11x4	7,33	o	o
DN 80	3"	76	205	160	106	250	12	17	F07	70	9x4	F10	102	11x4	10,49	o	o

nr	part name	naam onderdeel	CF8	CF8M	pc
			304	316	st
1	body	huis	ASTM A 351 CF8	ASTM A 351 CF8M	1
2	ball	kogel	ASTM A 182 F316	ASTM A 182 F316	1
3	Seat	zitting	PTFE	PTFE	2
4	Gasket	pakking	PTFE	PTFE	2
5	End-Cap	eindkap	ASTM A 351 CF8	ASTM A 351 CF8M	1
9	plunger spring	plunjer veer	ASTM 276 SS316	ASTM 276 SS316	2
10	anti static ball	antistatischekogel	ASTM 276 SS316	ASTM 276 SS316	2
11	stem	spindel	ASTM 276 SS316	ASTM 276 SS316	1
12	thrust washer	dichtingsring	PTFE	PTFE	1
13	o ring	o ring	VITON	VITON	1
14	stem packing	spindelpakking	PTFE	PTFE	1
15	gland	pakkingsdrukker	ASTM 276 SS304	ASTM 276 SS304	1
16	Bellvile washer	schotelring	A2-70 (SS304)	A2-70 (SS304)	2
17	crown washer	kroonring	ASTM 240 tp 304	ASTM 240 tp 304	1
18	spring washer	veerring	ASTM 276 SS304	ASTM 276 SS304	2
19	stem nut	spindelmoer	A2-70 (SS304)	A2-70 (SS304)	2
20	handle stop bold	hendel stoppin	A2-70 (SS304)	A2-70 (SS304)	1
21	locking pad	vergrendeling	ASTM A 240 tp 201	ASTM A 240 tp 201	1
22	handle	hendel	ASTM A 240 tp 201	ASTM A 240 tp 201	1
23	handle cover	handgreep	PVC	PVC	1
24	handle stop nut	hendel stopmoer	A2-70 (SS304)	A2-70 (SS304)	1

- stock, s.u.
 - o ex mill
-
- voorraad, m.o.
 - o af fabriek

COLOUR LEVER : standard : yellow Options : red, green, blue, grey, white
 KLEUR HANDGREEP : standaard: geel. Opties : rood, groen, blauw, grijs, wit.



www.md-europe.eu

MDV-368T



pressure - temperature

druk - temperatuur

